


### Light Stripe Dali Version 900 mm

■ 03.7005.14.DA - Black

Diffused LED light module to be installed in The Running Magnet System. Opaline end caps to create continuous lines of light included.



#### Main specifications

|                |       |             |                     |
|----------------|-------|-------------|---------------------|
| Lamp category  | LED   | Mountings   | Track               |
| Power (W)      | 22.5W | Environment | Indoor dry location |
| CCT (K)        | 3000K |             |                     |
| CRI            | 90    |             |                     |
| Net lumen (lm) | 1320  |             |                     |

#### Optical

|                    |                |                        |     |
|--------------------|----------------|------------------------|-----|
| Lighting type      | Direct         | Beam angle C90-270 (°) | 105 |
| LED type           | Top LED        |                        |     |
| Light distribution | Symmetric      |                        |     |
| Optical type       | Diffused light |                        |     |
| Beam angle (°)     | 108            |                        |     |

#### Electrical

|             |                 |                  |     |
|-------------|-----------------|------------------|-----|
| Voltage (V) | 24.00           | Insulation class | III |
| Dimmable    | Yes             |                  |     |
| Driver      | Remote excluded |                  |     |
| Driver type | Dimmable DALI   |                  |     |
| Emergency   | Without         |                  |     |

#### Physical

|             |       |
|-------------|-------|
| Color       | Black |
| Orientation | Fixed |
| Weight (kg) | 1.02  |
| Length (mm) | 906   |

#### Note

For wireless lighting control, choose integrated Casambi versions. For the sizing of the installation keep a safety margin of 15% of the maximum power of the LED power source.

