


Light Supply Adjustable No Trim

■ 03.6618.14 - Black

Recessed luminaire with LED light source. Remote 220/240V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	1871
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	28W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	16°
Beam angle C90-270 (°)	16°



Beam Angle: 16°

h(m)	E(lx)	D(m)
1	14647	0.29
2	3662	0.58
3	1627	0.87
4	915	1.15
5	586	1.44

Luminous flux luminaire
1871 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		
Emergency	Without		

Physical

Color	Black	Rotation (°)	355
Orientation	Adjustable		
Recessed depth (mm)	239		
Weight (kg)	1.01		
Tilt (°)	35		

Note

Pre-installation frame or Soft Architecture installation plate for No Trim installation. Have to be ordered separately.



Light Supply Adjustable No Trim



Light Supply Adjustable spare reflector. Medium
08.8414.00

Soft Architecture installation plate
SA.6600.1


Honeycomb. Big Cells
08.8377.14



Honeycomb. Small Cells
08.8049.14

Light Supply Adjustable spare reflector. Spot
08.8413.00

Light Supply Adjustable spare reflector. Flood
08.8415.00



Screening crosspiece
08.8242.14

Elliptical lens
08.8118.68

Pre-installation frame
08.8119.00