


## Light Supply Adjustable No Trim

03.6621.40 - White

Recessed luminaire with LED light source. Remote 220/240V power supply included.




## Main specifications

Number of heads	1	Net lumen (lm)	1363
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	26W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	98		

## Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	16
Beam angle C90-270 (°)	16



Beam Angle: 16°

h(m)	E(lx)	D(m)
1	11064	0.28
2	2766	0.56
3	1229	0.84
4	692	1.12
5	443	1.40

Luminous flux luminaire  
1363 lm (EXTREME CUT OFF)

## Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

## Physical

Color	White	Rotation (°)	355
Orientation	Adjustable		
Recessed depth (mm)	239		
Weight (kg)	1.01		
Tilt (°)	35		

## Note

Pre-installation frame or Soft Architecture installation plate for No Trim installation. Have to be ordered separately.



## Light Supply Adjustable No Trim



---

Light Supply Adjustable spare  
reflector. Medium  
08.8414.00



---

Screening crosspiece  
08.8242.14



---

Elliptical lens  
08.8118.68



---

Pre-installation frame  
08.8119.00



---

Honeycomb. Big Cells  
08.8377.14



---

Honeycomb. Small Cells  
08.8049.14



---

Light Supply Adjustable spare  
reflector. Spot  
08.8413.00



---

Light Supply Adjustable spare  
reflector. Flood  
08.8415.00



---

Soft Architecture installation plate  
SA.6600.1