


Light Supply Adjustable No Trim

03.6815.40A - White

Recessed luminaire with LED light source. Remote 220/240V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	2208
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	30.1W	Environment	Indoor
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	13
Beam angle C90-270 (°)	13



Beam Angle:	13°		
h(m)	E(lx)	D(m)	
1	26681	0.23	
2	6670	0.46	
3	2965	0.69	
4	1668	0.92	
5	1067	1.15	

Luminous flux luminaire
2208 lm (EXTREME CUT OFF)

Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	37.60	Insulation class	II
Dimmable	No		
Driver	Remote		
Driver type	Electronic		

Physical

Color	White	Rotation (°)	355
Orientation	Adjustable		
Recessed depth (mm)	239		
Weight (kg)	1.01		
Tilt (°)	35		

Note

Pre-installation frame or Soft Architecture installation plate for No Trim installation. To be ordered separately.



Light Supply Adjustable No Trim



Light Supply Adjustable spare reflector. Spot
08.8450.00



Elliptical lens
08.8118.68



Screening crosspiece
08.8242.14



Honeycomb. Small Cells
08.8049.14



Honeycomb. Big Cells
08.8377.14



Highly-efficient cylinder
08.8453.40



Light Supply Adjustable spare reflector. Flood
08.8452.00



Light Supply Adjustable spare reflector. Medium
08.8451.00



Pre-installation frame
08.8119.00



Soft Architecture installation plate
SA.6600.1