


## Light Supply Adjustable No Trim

03.6818.40A - White

Recessed luminaire with LED light source. Remote 220/240V power supply included.




## Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 1846                |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 30.1W | Environment    | Indoor dry location |
| CCT (K)         | 4000K |                |                     |
| CRI             | 90    |                |                     |

## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 13        |
| Beam angle C90-270 (°) | 13        |



Beam Angle: 13°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 22306 | 0.23 |
| 2    | 5576  | 0.46 |
| 3    | 2478  | 0.69 |
| 4    | 1394  | 0.92 |
| 5    | 892   | 1.15 |

Luminous flux luminaire  
1846 lm (EXTREME CUT OFF)

## Electrical

|                |                 |                  |         |
|----------------|-----------------|------------------|---------|
| Frequency (Hz) | 50/60           | Emergency        | Without |
| Voltage (V)    | 37.60           | Insulation class | II      |
| Dimmable       | No              |                  |         |
| Driver         | Remote included |                  |         |
| Driver type    | Non Dimmable    |                  |         |

## Physical


|                     |            |              |     |
|---------------------|------------|--------------|-----|
| Color               | White      | Rotation (°) | 355 |
| Orientation         | Adjustable |              |     |
| Recessed depth (mm) | 239        |              |     |
| Weight (kg)         | 1.01       |              |     |
| Tilt (°)            | 35         |              |     |

## Note

Pre-installation frame or Soft Architecture installation plate for No Trim installation. To be ordered separately.



Light Supply Adjustable No Trim



Pre-installation frame  
08.8119.00



Soft Architecture installation plate  
SA.6600.1



Light Supply Adjustable spare  
reflector. Spot  
08.8450.00



Light Supply Adjustable spare  
reflector. Flood  
08.8452.00



Honeycomb. Big Cells  
08.8377.14



Honeycomb. Small Cells  
08.8049.14



Screening crosspiece  
08.8242.14



Elliptical lens  
08.8118.68



Light Supply Adjustable spare  
reflector. Medium  
08.8451.00



---

Highly-efficient cylinder  
08.8453.40