


## Light Supply Adjustable No Trim

■ 03.6819.14A - Black

Recessed luminaire with LED light source. Remote 220/240V power supply included.




## Main specifications

Number of heads	1	Net lumen (lm)	1486
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	30.1W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	90		

## Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	21
Beam angle C90-270 (°)	21



Beam Angle: 21°

h(m)	E(lx)	D(m)
1	8164	0.37
2	2041	0.75
3	907	1.12
4	510	1.49
5	327	1.87

Luminous flux luminaire  
1486 lm (EXTREME CUT OFF)

## Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	37.60	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

## Physical

Color	Black	Rotation (°)	355
Orientation	Adjustable		
Recessed depth (mm)	239		
Weight (kg)	1.01		
Tilt (°)	35		

## Note

Pre-installation frame or Soft Architecture installation plate for No Trim installation. To be ordered separately.



Light Supply Adjustable No Trim



Light Supply Adjustable spare reflector. Medium  
08.8451.00



Highly-efficient cylinder  
08.8453.40



Honeycomb. Big Cells  
08.8377.14



Soft Architecture installation plate  
SA.6600.1



Pre-installation frame  
08.8119.00



Light Supply Adjustable spare reflector. Spot  
08.8450.00



Light Supply Adjustable spare reflector. Flood  
08.8452.00



Honeycomb. Small Cells  
08.8049.14



Screening crosspiece  
08.8242.14



---

Elliptical lens  
08.8118.68