Light Supply Adjustable No Trim

03.6823.14A - Black

Recessed luminaire with LED light source. Remote 220/240V power supply included.



Main specifications

Number of heads	1	**Net lumen (lm)**	1508
Lamp category	LED	**Mountings**	Ceiling recessed
Power (W)	30.1W	**Environment**	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	39
Beam angle C90-270 (°)	39



Luminous flux luminaire
1508 lm (EXTREME CUT OFF)

Beam Angle: 39°

h(m)	E(lx)	D(m)
1	4225	0.71
2	1056	1.42
3	469	2.14
4	264	2.85
5	169	3.56

Electrical

Frequency (Hz)	50/60	**Emergency**	Without
Voltage (V)	37.60	**Insulation class**	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

Physical

Color	Black	**Rotation (°)**	355
Orientation	Adjustable		
Recessed depth (mm)	239		
Weight (kg)	1.01		
Tilt (°)	35		

Note

Pre-installation frame or Soft Architecture installation plate for No Trim installation. To be ordered separately.

Light Supply Adjustable No Trim

Light Supply Adjustable spare reflector. Medium
08.8451.00

Highly-efficient cylinder
08.8453.40

Honeycomb. Big Cells
08.8377.14

Soft Architecture installation plate
SA.6600.1

Pre-installation frame
08.8119.00

Light Supply Adjustable spare reflector. Spot
08.8450.00

Light Supply Adjustable spare reflector. Flood
08.8452.00

Honeycomb. Small Cells
08.8049.14

Screening crosspiece
08.8242.14

Elliptical lens
08.8118.68