


## Light Supply Adjustable No Trim Dimmable

■ 03.6620.14.DA - Black

Recessed luminaire with LED light source. Remote 220/240V power supply included.




## Main specifications

Number of heads	1	Net lumen (lm)	1725
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	28W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

## Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	33
Beam angle C90-270 (°)	33



Beam Angle: 33°

h(m)	E(lx)	D(m)
1	5127	0.60
2	1282	1.19
3	570	1.79
4	320	2.39
5	205	2.99

Luminous flux luminaire  
1725 lm (EXTREME CUT OFF)

## Electrical

Frequency (Hz)	50/60	Insulation class	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable 1-10V, Dimmable DALI 1		
Emergency	Without		

## Physical

Color	Black	Rotation (°)	355
Orientation	Adjustable		
Recessed depth (mm)	239		
Weight (kg)	1.01		
Tilt (°)	35		

## Note

Pre-installation frame or Soft Architecture installation plate for No Trim installation. Have to be ordered separately.

## Light Supply Adjustable No Trim Dimmable



---

Light Supply Adjustable spare  
reflector. Spot  
08.8413.00



---

Light Supply Adjustable spare  
reflector. Flood  
08.8415.00



---

Soft Architecture installation plate  
SA.6600.1



---

Pre-installation frame  
08.8119.00



---

Honeycomb. Small Cells  
08.8049.14



---

Light Supply Adjustable spare  
reflector. Medium  
08.8414.00



---

Screening crosspiece  
08.8242.14



---

Elliptical lens  
08.8118.68



---

Honeycomb. Big Cells  
08.8377.14