Light Supply Adjustable No Trim Dimmable

03.6622.14.DA - Black

Recessed luminaire with LED light source. Remote 220/240V power supply included.



Main specifications

Number of heads	1	**Net lumen (lm)**	1297
Lamp category	LED	**Mountings**	Ceiling recessed
Power (W)	26W	**Environment**	Indoor dry location
CCT (K)	3000K		
CRI	98		

Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	24
Beam angle C90-270 (°)	24



Luminous flux luminaire
1297 lm (EXTREME CUT OFF)

Beam Angle: 24°

h(m)	E(lx)	D(m)
1	6500	0.42
2	1625	0.84
3	722	1.27
4	406	1.69
5	260	2.11

Electrical

Frequency (Hz)	50/60	**Emergency**	Without
Voltage (V)	220.00	**Insulation class**	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable 1-10V, Dimmable DALI 1		

Physical

Color	Black	**Rotation (°)**	355
Orientation	Adjustable		
Recessed depth (mm)	239		
Weight (kg)	1.01		
Tilt (°)	35		

Note

Pre-installation frame or Soft Architecture installation plate for No Trim installation. Have to be ordered separately.

Light Supply Adjustable No Trim Dimmable

Light Supply Adjustable spare reflector. Medium
08.8414.00

Screening crosspiece
08.8242.14

Elliptical lens
08.8118.68

Soft Architecture installation plate
SA.6600.1

Light Supply Adjustable spare reflector. Spot
08.8413.00

Light Supply Adjustable spare reflector. Flood
08.8415.00

Honeycomb. Big Cells
08.8377.14

Honeycomb. Small Cells
08.8049.14

Pre-installation frame
08.8119.00