


Light Supply Adjustable No Trim Dimmable

■ 03.6815.14ADA - Black

Recessed luminaire with LED light source. Remote 220/240V power supply included.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 2208 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 30.1W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 80 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 13 |
| Beam angle C90-270 (°) | 13 |



| | | | |
|--------------------|--------------|-------------|--|
| Beam Angle: | 13° | | |
| h(m) | E(lx) | D(m) | |
| 1 | 26681 | 0.23 | |
| 2 | 6670 | 0.46 | |
| 3 | 2965 | 0.69 | |
| 4 | 1668 | 0.92 | |
| 5 | 1067 | 1.15 | |

Luminous flux luminaire
2208 lm (EXTREME CUT OFF)

Electrical


| | | | |
|-----------------------|---------------------------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 37.60 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote included | | |
| Driver type | Dimmable 1-10V, Dimmable DALI 1 | | |

Physical

| | | | |
|----------------------------|------------|---------------------|-----|
| Color | Black | Rotation (°) | 355 |
| Orientation | Adjustable | | |
| Recessed depth (mm) | 239 | | |
| Weight (kg) | 1.01 | | |
| Tilt (°) | 35 | | |

Note

Pre-installation frame or Soft Architecture installation plate for No Trim installation. To be ordered separately.



Light Supply Adjustable No Trim Dimmable



Light Supply Adjustable spare reflector. Medium
08.8451.00



Highly-efficient cylinder
08.8453.40



Honeycomb. Big Cells
08.8377.14



Honeycomb. Small Cells
08.8049.14



Pre-installation frame
08.8119.00



Light Supply Adjustable spare reflector. Spot
08.8450.00



Light Supply Adjustable spare reflector. Flood
08.8452.00



Screening crosspiece
08.8242.14



Elliptical lens
08.8118.68



Soft Architecture installation plate
SA.6600.1