


Light Supply Adjustable No Trim Dimmable

03.6817.40ADA - White

Recessed luminaire with LED light source. Remote 220/240V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	1960
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	30.1W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	39
Beam angle C90-270 (°)	39



Beam Angle: 39°

h(m)	E(lx)	D(m)
1	5493	0.71
2	1373	1.42
3	610	2.14
4	343	2.85
5	220	3.56

Luminous flux luminaire
1960 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	37.60	Insulation class	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable 1-10V, Dimmable DALI 1		

Physical

Color	White	Rotation (°)	355
Orientation	Adjustable		
Recessed depth (mm)	239		
Weight (kg)	1.01		
Tilt (°)	35		

Note

Pre-installation frame or Soft Architecture installation plate for No Trim installation. To be ordered separately.

Light Supply Adjustable No Trim Dimmable



Soft Architecture installation plate
SA.6600.1




Light Supply Adjustable spare
reflector. Spot
08.8450.00



Light Supply Adjustable spare
reflector. Flood
08.8452.00



Elliptical lens
08.8118.68



Pre-installation frame
08.8119.00



Honeycomb. Big Cells
08.8377.14



Honeycomb. Small Cells
08.8049.14



Screening crosspiece
08.8242.14



Light Supply Adjustable spare
reflector. Medium
08.8451.00



Highly-efficient cylinder
08.8453.40