


Light Supply Adjustable No Trim Dimmable

03.6823.40ADA - White

Recessed luminaire with LED light source. Remote 220/240V power supply included.




Main specifications

| | | | |
|------------------------|-------|-----------------------|------------------|
| Number of heads | 1 | Net lumen (lm) | 1508 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 30.1W | Environment | Indoor |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 39 |
| Beam angle C90-270 (°) | 39 |



| Beam Angle: 39° | | |
|-----------------|-------|------|
| h(m) | E(lx) | D(m) |
| 1 | 4225 | 0.71 |
| 2 | 1056 | 1.42 |
| 3 | 469 | 2.14 |
| 4 | 264 | 2.85 |
| 5 | 169 | 3.56 |

Luminous flux luminaire
1508 lm (EXTREME CUT OFF)

Electrical


| | | | |
|-----------------------|---|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 37.60 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote | | |
| Driver type | Electronic dimmable 1-10V, Electronic dimmable DALI | | |

Physical

| | | | |
|----------------------------|------------|---------------------|-----|
| Color | White | Rotation (°) | 355 |
| Orientation | Adjustable | | |
| Recessed depth (mm) | 239 | | |
| Weight (kg) | 1.01 | | |
| Tilt (°) | 35 | | |

Note

Pre-installation frame or Soft Architecture installation plate for No Trim installation. To be ordered separately.



Light Supply Adjustable No Trim Dimmable



Light Supply Adjustable spare reflector. Spot
08.8450.00



Elliptical lens
08.8118.68



Screening crosspiece
08.8242.14



Honeycomb. Small Cells
08.8049.14



Honeycomb. Big Cells
08.8377.14



Highly-efficient cylinder
08.8453.40



Light Supply Adjustable spare reflector. Flood
08.8452.00



Light Supply Adjustable spare reflector. Medium
08.8451.00



Pre-installation frame
08.8119.00



Soft Architecture installation plate
SA.6600.1