



03.6806.14A - Black

Recessed luminaire with LED light source. Remote 220/240V power supply included.



Number of heads	1	Net lumen (lm)	1698
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	30.1W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	13
Beam angle C90-270 (°)	13



Beam Angle: 13°

h(m)	E(lx)	D(m)
1	20522	0.23
2	5131	0.46
3	2280	0.69
4	1283	0.92
5	821	1.15

Luminous flux lumineuse  
1698 lm (EXTREME CUT OFF)

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	37.60	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

Color	Black	Rotation (°)	355
Orientation	Adjustable		
Recessed depth (mm)	239		
Weight (kg)	1.01		
Tilt (°)	35		

# Light Supply Adjustable Trim



Honeycomb. Big Cells  
08.8377.14

Light Supply Adjustable spare  
reflector. Medium  
08.8451.00

Highly-efficient cylinder  
08.8453.40



Honeycomb. Small Cells  
08.8049.14

Screening crosspiece  
08.8242.14

Elliptical lens  
08.8118.68



Light Supply Adjustable spare  
reflector. Spot  
08.8450.00

Light Supply Adjustable spare  
reflector. Flood  
08.8452.00