



03.6806.40A - White

Recessed luminaire with LED light source. Remote 220/240V power supply included.



|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 1698                |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 30.1W | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 90    |                |                     |

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 13        |
| Beam angle C90-270 (°) | 13        |



Beam Angle: 13°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 20522 | 0.23 |
| 2    | 5131  | 0.46 |
| 3    | 2280  | 0.69 |
| 4    | 1283  | 0.92 |
| 5    | 821   | 1.15 |

Luminous flux lumineire  
1698 lm (EXTREME CUT OFF)

|                |                 |                  |         |
|----------------|-----------------|------------------|---------|
| Frequency (Hz) | 50/60           | Emergency        | Without |
| Voltage (V)    | 37.60           | Insulation class | II      |
| Dimmable       | No              |                  |         |
| Driver         | Remote included |                  |         |
| Driver type    | Non Dimmable    |                  |         |

|                     |            |              |     |
|---------------------|------------|--------------|-----|
| Color               | White      | Rotation (°) | 355 |
| Orientation         | Adjustable |              |     |
| Recessed depth (mm) | 239        |              |     |
| Weight (kg)         | 1.01       |              |     |
| Tilt (°)            | 35         |              |     |

Light Supply Adjustable Trim



Honeycomb. Big Cells  
08.8377.14

Light Supply Adjustable spare  
reflector. Medium  
08.8451.00

Highly-efficient cylinder  
08.8453.40



Honeycomb. Small Cells  
08.8049.14

Light Supply Adjustable spare  
reflector. Spot  
08.8450.00

Light Supply Adjustable spare  
reflector. Flood  
08.8452.00



Screening crosspiece  
08.8242.14

Elliptical lens  
08.8118.68