


### Light Supply Adjustable Trim

03.6807.40A - White

Recessed luminaire with LED light source. Remote 220/240V power supply included.




#### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 1367                |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 30.1W | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 90    |                |                     |

#### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 21        |
| Beam angle C90-270 (°) | 21        |



|             |              |             |
|-------------|--------------|-------------|
| Beam Angle: | 21°          |             |
| <u>h(m)</u> | <u>E(lx)</u> | <u>D(m)</u> |
| 1           | 7511         | 0.37        |
| 2           | 1878         | 0.75        |
| 3           | 835          | 1.12        |
| 4           | 469          | 1.49        |
| 5           | 300          | 1.87        |

Luminous flux luminaire  
1367 lm (EXTREME CUT OFF)

#### Electrical

|                |                 |                  |         |
|----------------|-----------------|------------------|---------|
| Frequency (Hz) | 50/60           | Emergency        | Without |
| Voltage (V)    | 37.60           | Insulation class | II      |
| Dimmable       | No              |                  |         |
| Driver         | Remote included |                  |         |
| Driver type    | Non Dimmable    |                  |         |

#### Physical

|                     |            |              |     |
|---------------------|------------|--------------|-----|
| Color               | White      | Rotation (°) | 355 |
| Orientation         | Adjustable |              |     |
| Recessed depth (mm) | 239        |              |     |
| Weight (kg)         | 1.01       |              |     |
| Tilt (°)            | 35         |              |     |



Light Supply Adjustable Trim



Light Supply Adjustable spare reflector. Spot  
08.8450.00



Light Supply Adjustable spare reflector. Flood  
08.8452.00



Honeycomb. Big Cells  
08.8377.14



Light Supply Adjustable spare reflector. Medium  
08.8451.00



Highly-efficient cylinder  
08.8453.40



Honeycomb. Small Cells  
08.8049.14



Screening crosspiece  
08.8242.14



Elliptical lens  
08.8118.68