


**Light Supply Adjustable Trim Dimmable**

03.6605.40.DA - White

Recessed luminaire with LED light source. Remote 220/240V power supply included.




## Main specifications

|                        |       |                       |                     |
|------------------------|-------|-----------------------|---------------------|
| <b>Number of heads</b> | 1     | <b>Net lumen (lm)</b> | 1725                |
| <b>Lamp category</b>   | LED   | <b>Mountings</b>      | Ceiling recessed    |
| <b>Power (W)</b>       | 28W   | <b>Environment</b>    | Indoor dry location |
| <b>CCT (K)</b>         | 4000K |                       |                     |
| <b>CRI</b>             | 80    |                       |                     |

## Optical

|                        |              |
|------------------------|--------------|
| Lighting type          | Direct       |
| LED type               | Phosphor LED |
| Light distribution     | Symmetric    |
| Optical type           | Flood        |
| Beam angle (°)         | 33           |
| Beam angle C90-270 (°) | 33           |



|             |              |             |  |
|-------------|--------------|-------------|--|
| Beam Angle: | 33°          |             |  |
| <u>h(m)</u> | <u>E(lx)</u> | <u>D(m)</u> |  |
| 1           | 5127         | 0.60        |  |
| 2           | 1282         | 1.19        |  |
| 3           | 570          | 1.79        |  |
| 4           | 320          | 2.39        |  |
| 5           | 205          | 2.99        |  |

Luminous flux lumineire  
1725 lm (EXTREME CUT OFF)

## Electrical

|                       |                                 |                         |    |
|-----------------------|---------------------------------|-------------------------|----|
| <b>Frequency (Hz)</b> | 50/60                           | <b>Insulation class</b> | II |
| <b>Dimmable</b>       | Yes                             |                         |    |
| <b>Driver</b>         | Remote included                 |                         |    |
| <b>Driver type</b>    | Dimmable 1-10V, Dimmable DALI 1 |                         |    |
| <b>Emergency</b>      | Without                         |                         |    |

## Physical

|                     |            |              |     |
|---------------------|------------|--------------|-----|
| Color               | White      | Rotation (°) | 355 |
| Orientation         | Adjustable |              |     |
| Recessed depth (mm) | 239        |              |     |
| Weight (kg)         | 1.01       |              |     |
| Tilt (°)            | 35         |              |     |

## Light Supply Adjustable Trim Dimmable



---

Elliptical lens  
08.8118.68



---

Screening crosspiece  
08.8242.14



---

Light Supply Adjustable spare  
reflector. Medium  
08.8414.00



---

Honeycomb. Small Cells  
08.8049.14



---

Honeycomb. Big Cells  
08.8377.14



---

Light Supply Adjustable spare  
reflector. Spot  
08.8413.00



---

Light Supply Adjustable spare  
reflector. Flood  
08.8415.00