


Light Supply Adjustable Trim Dimmable

■ 03.6806.14ADA - Black

Recessed luminaire with LED light source. Remote 220/240V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	1698
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	30.1W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	13
Beam angle C90-270 (°)	13



Beam Angle:	13°		
h(m)	E(lx)	D(m)	
1	20522	0.23	
2	5131	0.46	
3	2280	0.69	
4	1283	0.92	
5	821	1.15	


Luminous flux luminaire
1698 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	37.60	Insulation class	II
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic dimmable 1-10V, Electronic dimmable DALI		

Physical

Color	Black	Rotation (°)	355
Orientation	Adjustable		
Recessed depth (mm)	239		
Weight (kg)	1.01		
Tilt (°)	35		



Light Supply Adjustable Trim Dimmable



Light Supply Adjustable spare reflector. Spot
08.8450.00



Elliptical lens
08.8118.68



Screening crosspiece
08.8242.14



Honeycomb. Small Cells
08.8049.14



Honeycomb. Big Cells
08.8377.14



Highly-efficient cylinder
08.8453.40



Light Supply Adjustable spare reflector. Flood
08.8452.00



Light Supply Adjustable spare reflector. Medium
08.8451.00