



03.6808.14ADA - Black

Recessed luminaire with LED light source. Remote 220/240V power supply included.



Number of heads	1	Net lumen (lm)	1508
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	30.1W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	39
Beam angle C90-270 (°)	39



Beam Angle: 39°

h(m)	E(lx)	D(m)
1	4225	0.71
2	1056	1.42
3	469	2.14
4	264	2.85
5	169	3.56

Luminous flux lumineuse
1508 lm (EXTREME CUT OFF)

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	37.60	Insulation class	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable 1-10V, Dimmable DALI 1		

Color	Black	Rotation (°)	355
Orientation	Adjustable		
Recessed depth (mm)	239		
Weight (kg)	1.01		
Tilt (°)	35		

Light Supply Adjustable Trim Dimmable



Light Supply Adjustable spare reflector. Spot
08.8450.00



Light Supply Adjustable spare reflector. Flood
08.8452.00



Honeycomb. Big Cells
08.8377.14



Honeycomb. Small Cells
08.8049.14



Screening crosspiece
08.8242.14



Elliptical lens
08.8118.68



Light Supply Adjustable spare reflector. Medium
08.8451.00



Highly-efficient cylinder
08.8453.40