


## Light Supply Fixed No Trim

■ 03.6625.06 - Aluminum

Recessed luminaire with LED light source. Remote 220/240V power supply included.




## Main specifications

Number of heads	1	Net lumen (lm)	2270
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	28W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

## Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Beam angle (°)	49
Beam angle C90-270 (°)	49



Beam Angle: 49°

h(m)	E(lx)	D(m)
1	3265	0.91
2	816	1.81
3	363	2.72
4	204	3.62
5	131	4.53

Luminous flux luminaire  
2270 lm (EXTREME CUT OFF)

## Electrical

Frequency (Hz)	50/60	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		
Emergency	Without		

## Physical

Color	Aluminum
Orientation	Fixed
Recessed depth (mm)	277
Weight (kg)	0.98

## Note

Pre-installation frame. To be ordered separately.



Light Supply Fixed No Trim



---

Soft Architecture installation plate  
SA.6610.1

---

Pre-installation frame  
08.8359.00