


Light Supply Fixed No Trim

■ 03.6824.06A - Aluminum

Recessed luminaire with LED light source. Remote 220/240V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	2123
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	29W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	47
Beam angle C90-270 (°)	47



Beam Angle:	47°		
h(m)	E(lx)	D(m)	
1	3248	0.86	
2	812	1.73	
3	361	2.59	
4	203	3.46	
5	130	4.32	

Luminous flux luminaire
2123 lm (EXTREME CUT OFF)

Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

Physical

Color	Aluminum
Orientation	Fixed
Recessed depth (mm)	277
Weight (kg)	0.98

Note

Pre-installation frame. To be ordered separately.



Light Supply Fixed No Trim



Pre-installation frame
08.8359.00