



Light Supply Fixed No Trim

03.6824.40A - White

Recessed luminaire with LED light source. Remote 220/240V power supply included.

Main specifications


| Number of heads | 1 |
|-----------------|-------|
| Lamp category | LED |
| Power (W) | 29W |
| CCT (K) | 3000K |
| CRI | 80 |

Net lumen (lm) 1799 Mountings

Ceiling recessed Environment Indoor dry location

Optical

| Lighting type | Direct |
|------------------------|-----------|
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 62 |
| Beam angle C90-270 (°) | 62 |



Luminous flux luminaire 1799 lm (EXTREME CUT OFF)

| Beam Angle: | | 62° |
|-------------|-------|------|
| h(m) | E(lx) | D(m) |
| 1 | 1805 | 1.19 |
| 2 | 451 | 2.39 |
| 3 | 201 | 3.58 |
| 4 | 113 | 4.77 |
| 5 | 72 | 5.97 |

Electrical

| Frequency (Hz) | 50/60 | Emergency | Without |
|----------------|-----------------|------------------|---------|
| Voltage (V) | 36.50 | Insulation class | II |
| Dimmable | No | | |
| Driver | Remote included | | |

Non Dimmable

Physical

Driver type

| Color | White |
|---------------------|-------|
| Orientation | Fixed |
| Recessed depth (mm) | 277 |
| Weight (kg) | 0.98 |

Note

 $\hbox{\it Pre-installation frame. To be ordered separately}.$

Light Supply Fixed No Trim



Pre-installation frame 08.8359.00