


## Light Supply Fixed No Trim

■ 03.6826.06A - Aluminum

Recessed luminaire with LED light source. Remote 220/240V power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1755
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	29W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	47
<b>Beam angle C90-270 (°)</b>	47



<b>Beam Angle:</b>	47°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	2684	0.86	
2	671	1.73	
3	298	2.59	
4	168	3.46	
5	107	4.32	

Luminous flux luminaire  
1755 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	No		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic		

### Physical

<b>Color</b>	Aluminum
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	277
<b>Weight (kg)</b>	0.98

### Note

Pre-installation frame. To be ordered separately.

## Light Supply Fixed No Trim



---

Pre-installation frame  
08.8359.00