



## Light Supply Fixed No Trim Dimmable

■ 03.6625.06.DA - Aluminum

Recessed luminaire with LED light source. Remote 220/240V power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2270
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	28W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	4000K		
<b>CRI</b>	80		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Phosphor LED
<b>Light distribution</b>	Symmetric
<b>Beam angle (°)</b>	49
<b>Beam angle C90-270 (°)</b>	49



Beam Angle: 49°

h(m)	E(lx)	D(m)
1	3265	0.91
2	816	1.81
3	363	2.72
4	204	3.62
5	131	4.53

Luminous flux luminaire  
2270 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic dimmable 1-10V, Electronic dimmable DALI		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Aluminum
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	277
<b>Weight (kg)</b>	0.98

### Note

Pre-installation frame. To be ordered separately.

## Light Supply Fixed No Trim Dimmable



---

Pre-installation frame  
08.8359.00

---

Soft Architecture installation plate  
SA.6610.1