


Light Supply Fixed No Trim Dimmable

03.6625.40.DA - White

Recessed luminaire with LED light source. Remote 220/240V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	1696
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	28W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Beam angle (°)	65
Beam angle C90-270 (°)	65



Beam Angle: 65°

h(m)	E(lx)	D(m)
1	1558	1.27
2	390	2.55
3	173	3.82
4	97	5.10
5	62	6.37

Luminous flux luminaire
1696 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Insulation class	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable 1-10V, Dimmable DALI 1		
Emergency	Without		

Physical

Color	White
Orientation	Fixed
Recessed depth (mm)	277
Weight (kg)	0.98

Note

Pre-installation frame. To be ordered separately.

Light Supply Fixed No Trim Dimmable



Soft Architecture installation plate
SA.6610.1

Pre-installation frame
08.8359.00