



Light Supply Fixed No Trim Dimmable

■ 03.6626.06.DA - Aluminum

Recessed luminaire with LED light source. Remote 220/240V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	1576
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	26W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	98		

Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Beam angle (°)	49
Beam angle C90-270 (°)	49



Beam Angle: 49°

h(m)	E(lx)	D(m)
1	2264	0.91
2	566	1.81
3	252	2.72
4	142	3.63
5	91	4.54

Luminous flux luminaire
1576 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable 1-10V, Dimmable DALI 1		

Physical

Color	Aluminum
Orientation	Fixed
Recessed depth (mm)	277
Weight (kg)	0.98

Note

Pre-installation frame. To be ordered separately.

Light Supply Fixed No Trim Dimmable



Pre-installation frame
08.8359.00

Soft Architecture installation plate
SA.6610.1