


## Light Supply Fixed No Trim Dimmable

03.6824.40ADA - White

Recessed luminaire with LED light source. Remote 220/240V power supply included.




### Main specifications

Number of heads	1	Net lumen (lm)	1799
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	29W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	62
Beam angle C90-270 (°)	62



Beam Angle: 62°

h(m)	E(lx)	D(m)
1	1805	1.19
2	451	2.39
3	201	3.58
4	113	4.77
5	72	5.97

Luminous flux luminaire  
1799 lm (EXTREME CUT OFF)

### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	36.50	Insulation class	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable 1-10V, Dimmable DALI 1		

### Physical

Color	White
Orientation	Fixed
Recessed depth (mm)	277
Weight (kg)	0.98

### Note

Pre-installation frame. To be ordered separately.



## Light Supply Fixed No Trim Dimmable



---

Pre-installation frame

08.8359.00