


## Light Supply Fixed No Trim Dimmable

■ 03.6826.06ADA - Aluminum

Recessed luminaire with LED light source. Remote 220/240V power supply included.




## Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 1755                |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 29W   | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 90    |                |                     |

## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 47        |
| Beam angle C90-270 (°) | 47        |



Beam Angle: 47°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 2684  | 0.86 |
| 2    | 671   | 1.73 |
| 3    | 298   | 2.59 |
| 4    | 168   | 3.46 |
| 5    | 107   | 4.32 |

Luminous flux luminaire  
1755 lm (EXTREME CUT OFF)

## Electrical

|                |                                 |                  |         |
|----------------|---------------------------------|------------------|---------|
| Frequency (Hz) | 50/60                           | Emergency        | Without |
| Voltage (V)    | 220.00                          | Insulation class | II      |
| Dimmable       | Yes                             |                  |         |
| Driver         | Remote included                 |                  |         |
| Driver type    | Dimmable 1-10V, Dimmable DALI 1 |                  |         |

## Physical

|                     |          |
|---------------------|----------|
| Color               | Aluminum |
| Orientation         | Fixed    |
| Recessed depth (mm) | 277      |
| Weight (kg)         | 0.98     |

## Note

Pre-installation frame. To be ordered separately.

## Light Supply Fixed No Trim Dimmable



---

Pre-installation frame  
08.8359.00