


## Light Supply Fixed Trim

03.6611.1C

Recessed luminaire with LED light source. Remote 220/240V power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1158
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	26W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	98		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Phosphor LED
<b>Light distribution</b>	Symmetric
<b>Beam angle (°)</b>	65
<b>Beam angle C90-270 (°)</b>	65



Beam Angle: 65°

	h(m)	E(lx)	D(m)
1	1.27	1069	1.27
2	2.54	267	2.54
3	3.80	119	3.80
4	5.07	67	5.07
5	6.34	43	6.34

Luminous flux luminaire  
1158 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	No		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic		

### Physical

<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	277
<b>Weight (kg)</b>	0.98

