


## Light Supply Fixed Trim

03.6811.3CA - White/Aluminium

Recessed luminaire with LED light source. Remote 220/240V power supply included.




## Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 1487                |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 29W   | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 90    |                |                     |

## Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | LED array |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 62        |
| Beam angle C90-270 (°) | 62        |



Beam Angle: 62°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 1492  | 1.19 |
| 2    | 373   | 2.39 |
| 3    | 166   | 3.58 |
| 4    | 93    | 4.77 |
| 5    | 60    | 5.97 |

Luminous flux luminaire  
1487 lm (EXTREME CUT OFF)

## Electrical

|                |                 |                  |         |
|----------------|-----------------|------------------|---------|
| Frequency (Hz) | 50/60           | Emergency        | Without |
| Voltage (V)    | 220.00          | Insulation class | II      |
| Dimmable       | No              |                  |         |
| Driver         | Remote included |                  |         |
| Driver type    | Non Dimmable    |                  |         |

## Physical

|                     |                 |
|---------------------|-----------------|
| Color               | White/Aluminium |
| Orientation         | Fixed           |
| Recessed depth (mm) | 277             |
| Weight (kg)         | 0.98            |