







# **Light Supply Fixed Trim Dimmable**

# 03.6611.1B.DA - Black/White

Recessed luminaire with LED light source. Remote 220/240V power supply included.

### Main specifications

Number of heads LED Lamp category Power (W) 26W CCT (K) 3000K CRI 98

Net lumen (lm) 1158

Mountings Ceiling recessed Environment Indoor dry location

#### Optical

Lighting type Direct LED type Phosphor LED Light distribution Symmetric Beam angle (°) 65 Beam angle C90-270 (°) 65

	X /	/X/	1	7
90°			-	000
		X	1	_ /
$\mathcal{X}$	////	H)	$\times$	7
60° ×	$\mathbb{Z}/ $	1 1	< €	000
$\perp \times \Lambda$	7	$\top$ $\setminus$	$\times$	
$\mathbb{K}^{\times}$	+	1	$\forall$	$\searrow$
	$X \perp$	X		/
		4	_\	
	' L	. \		$\times$
30°	1069	cd \	3	30°,
	CI.			

Luminous flux luminaire 1158 lm (EXTREME CUT OFF)

**Emergency** 

Insulation class

Without

Bear	Beam Angle:	
h(m)	E(lx)	D(m)
1	1069	1.27
2	267	2.54
3	119	3.80
4	67	5.07
5	43	6.34

### **Electrical**

Frequency (Hz) 50/60 Voltage (V) 220.00 Yes Dimmable

Driver Remote included Driver type Dimmable 1-10V, Dimmable

DALI 1

# Physical

Color Black/White Orientation Fixed Recessed depth (mm) 277 Weight (kg) 0.98