


Light Supply Fixed Trim Dimmable

■ ■ 03.6611.1C.DA - Black/Aluminium

Recessed luminaire with LED light source. Remote 220/240V power supply included.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 1158 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 26W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 98 | | |

Optical

| | |
|-------------------------------|--------------|
| Lighting type | Direct |
| LED type | Phosphor LED |
| Light distribution | Symmetric |
| Beam angle (°) | 65 |
| Beam angle C90-270 (°) | 65 |



| | | |
|------------------------|--------------|-------------|
| Beam Angle: 65° | | |
| h(m) | E(lx) | D(m) |
| 1 | 1069 | 1.27 |
| 2 | 267 | 2.54 |
| 3 | 119 | 3.80 |
| 4 | 67 | 5.07 |
| 5 | 43 | 6.34 |

Luminous flux luminaire
1158 lm (EXTREME CUT OFF)

Electrical

| | | | |
|-----------------------|---------------------------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote included | | |
| Driver type | Dimmable 1-10V, Dimmable DALI 1 | | |

Physical

| | |
|----------------------------|-----------------|
| Color | Black/Aluminium |
| Orientation | Fixed |
| Recessed depth (mm) | 277 |
| Weight (kg) | 0.98 |

