









Light Supply Fixed Trim Dimmable

03.6809.1BADA - Black/White

Recessed luminaire with LED light source. Remote 220/240V power supply included.

Main specifications

 Number of heads
 1

 Lamp category
 LED

 Power (W)
 29W

 CCT (K)
 3000K

 CRI
 80

Net lumen (lm) Mountings

Mountings Ceiling
Environment Indoor

1799

Ceiling recessed Indoor dry location

Optical

Lighting type Direct
LED type LED array
Light distribution Symmetric
Optical type Flood
Beam angle (°) 62
Beam angle C90-270 (°) 62

| | 1 |
|--------------------|---------------------------|
| 90° | 90°- |
| | 1 |
| | \checkmark \checkmark |
| 60° // \ \ \ \ \ | 60% |
| 1 X MHM | \times |
| | $<$ \setminus |
| | |
| | \prec |
| | |
| 30° √ 1805 cd \ | 30° |
| 1 . (1 1 | 50, |

Luminous flux luminaire 1799 lm (EXTREME CUT OFF)

| Beam Angle: | | 62° |
|-------------|----------------|------|
| h(m) | E(l x) | D(m |
| 1 | 1805 | 1.19 |
| 2 | 451 | 2.39 |
| 3 | 201 | 3.58 |
| 4 | 113 | 4.77 |
| 5 | 72 | 5 07 |

Electrical

Frequency (Hz) 50/60
Voltage (V) 36.50
Dimmable Yes

Driver Remote included
Driver type Dimmable 110V, Dimmable
DALI 1

Emergency Without Insulation class

Physical

ColorBlack/WhiteOrientationFixedRecessed depth (mm)277Weight (kg)0.98