









Light Supply Fixed Trim Dimmable

03.6810.3BADA - White/White

Recessed luminaire with LED light source. Remote 220/240V power supply included.

Main specifications

 Number of heads
 1

 Lamp category
 LED

 Power (W)
 29W

 CCT (K)
 4000K

 CRI
 90

Net lumen (lm) 1549 Mountings Ceilin

MountingsCeiling recessedEnvironmentIndoor dry location

Optical

Lighting type Direct
LED type LED array
Light distribution Symmetric
Optical type Flood
Beam angle (°) 62
Beam angle C90-270 (°) 62

	X / /	\times	1
90°			90°
			+
	////		<u> </u>
60° ×	\mathcal{H}	\mathcal{W}	606
	I/T	11	\times
K /	$\forall +$	+1	\mathbb{K}
	λ	1	\times
		-	
30° /	1554	cd \	30°
	- (1	i '	

Luminous flux luminaire 1549 lm (EXTREME CUT OFF)

Emergency

Insulation class

Without

Beam Angle:		62°
h(m)	E(lx)	D(m
1	1554	1.19
2	389	2.39
3	173	3.58
4	97	4.77
5	62	5 97

Electrical

 Frequency (Hz)
 50/60

 Voltage (V)
 36.50

 Dimmable
 Yes

Driver Remote included
Driver type Dimmable 110V, Dimmable

DALI 1

DALIT

Physical

Color White/White
Orientation Fixed
Recessed depth (mm) 277
Weight (kg) 0.98