

Light Supply Wall-Washer No Trim

■ 03.6629.06 - Aluminum


Recessed luminaire with LED light source. Remote 220/240V power supply included.

Main specifications

Number of heads	1	Net lumen (lm)	1401
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	26W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	98		

Optical

Lighting type	Indirect, Direct
LED type	Phosphor LED
Light distribution	Asymmetric
Optical type	Wall Washer
Beam angle (°)	35
Beam angle C90-270 (°)	48



Beam Angle: 35°

h(m)	E(lx)	D(m)
1	1881	0.71
2	470	1.41
3	209	2.12
4	118	2.83
5	75	3.53

Luminous flux luminaire
1401 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	No		
Driver	Remote included		
Driver type	Non Dimmable		

Physical

Color	Aluminum
Orientation	Fixed
Recessed depth (mm)	290
Weight (kg)	1.01

Note

Pre-installation frame. To be ordered separately.

Light Supply Wall-Washer No Trim



Pre-installation frame
08.8137.00



Soft Architecture installation plate
SA.6615.1