


## Light Supply Wall-Washer No Trim

■ 03.6829.06A - Aluminum

Recessed luminaire with LED light source. Remote 220/240V power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1909
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	33.2W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Indirect, Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Asymmetric
<b>Optical type</b>	Wall Washer
	Down
<b>Beam angle (°)</b>	34
<b>Beam angle C90-270 (°)</b>	48



<b>Beam Angle: 34°</b>		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	2588	0.67
2	647	1.35
3	288	2.02
4	162	2.69
5	104	3.37

Luminous flux luminaire  
1909 lm (EXTREME CUT OFF)

### Electrical


<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	No		
<b>Driver</b>	Remote included		
<b>Driver type</b>	Non Dimmable		

### Physical

<b>Color</b>	Aluminum
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	290
<b>Weight (kg)</b>	1.01

### Note

Pre-installation frame. To be ordered separately.



## Light Supply Wall-Washer No Trim



---

Pre-installation frame  
08.8137.00