

## Light Supply Wall-Washer No Trim Dimmable

■ 03.6628.06.DA - Aluminum


Recessed luminaire with LED light source. Remote 220/240V power supply included.

### Main specifications

Number of heads	1	Net lumen (lm)	1967
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	28W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

### Optical

Lighting type	Indirect, Direct
LED type	Phosphor LED
Light distribution	Asymmetric
Optical type	Wall Washer
Beam angle (°)	Down 35
Beam angle C90-270 (°)	50



Beam Angle: 35°

h(m)	E(lx)	D(m)
1	2634	0.70
2	658	1.40
3	293	2.10
4	165	2.79
5	105	3.49

Luminous flux luminaire  
1967 lm (EXTREME CUT OFF)

### Electrical

Frequency (Hz)	50/60	Insulation class	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable 1-10V, Dimmable DALI 1		
Emergency	Without		

### Physical

Color	Aluminum
Orientation	Fixed
Recessed depth (mm)	290
Weight (kg)	1.01

### Note

Pre-installation frame. To be ordered separately.

Light Supply Wall-Washer No Trim Dimmable



---

Soft Architecture installation plate  
SA.6615.1

---

Pre-installation frame  
08.8137.00