


Light Supply Wall-Washer No Trim Dimmable

■ 03.6629.06.DA - Aluminum

Recessed luminaire with LED light source. Remote 220/240V power supply included.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 1401 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 26W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 98 | | |

Optical

| | |
|-------------------------------|------------------|
| Lighting type | Indirect, Direct |
| LED type | Phosphor LED |
| Light distribution | Asymmetric |
| Optical type | Wall Washer |
| | Down |
| Beam angle (°) | 35 |
| Beam angle C90-270 (°) | 48 |



Beam Angle: 35°

| | h(m) | E(lx) | D(m) |
|---|------|-------|------|
| 1 | 1881 | 0.71 | |
| 2 | 470 | 1.41 | |
| 3 | 209 | 2.12 | |
| 4 | 118 | 2.83 | |
| 5 | 75 | 3.53 | |

Luminous flux luminaire
1401 lm (EXTREME CUT OFF)

Electrical


| | | | |
|-----------------------|---------------------------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote included | | |
| Driver type | Dimmable 1-10V, Dimmable DALI 1 | | |

Physical

| | |
|----------------------------|----------|
| Color | Aluminum |
| Orientation | Fixed |
| Recessed depth (mm) | 290 |
| Weight (kg) | 1.01 |

Note

Pre-installation frame. To be ordered separately.



Light Supply Wall-Washer No Trim Dimmable



Pre-installation frame
08.8137.00

Soft Architecture installation plate
SA.6615.1