

## Light Supply Wall-Washer No Trim Dimmable

03.6828.40ADA - White

Recessed luminaire with LED light source. Remote 220/240V power supply included.


Recessed luminaire with LED light source. Remote 220/240V power supply included.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1845
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	33.2W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	4000K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Indirect, Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Asymmetric
<b>Optical type</b>	Wall-washer
<b>Beam angle (°)</b>	36
<b>Beam angle C90-270 (°)</b>	51



Beam Angle: 36°

h(m)	E(lx)	D(m)
1	2179	0.74
2	545	1.48
3	242	2.22
4	136	2.95
5	87	3.69

Luminous flux luminaire  
1845 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic dimmable 1-10V, Electronic dimmable DALI		


### Physical

<b>Color</b>	White
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	290
<b>Weight (kg)</b>	1.01

### Note

Pre-installation frame. To be ordered separately.

### Certification / Marking



## Light Supply Wall-Washer No Trim Dimmable



---

Pre-installation frame  
08.8137.00