


### Light Supply Wall-Washer No Trim Dimmable

■ 03.6829.06ADA - Aluminum

Recessed luminaire with LED light source. Remote 220/240V power supply included.




#### Main specifications

Number of heads	1	Net lumen (lm)	1909
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	33.2W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

#### Optical

Lighting type	Indirect, Direct
LED type	LED array
Light distribution	Asymmetric
Optical type	Wall Washer
Beam angle (°)	Down
Beam angle C90-270 (°)	34
	48



Beam Angle: 34°

h(m)	E(lx)	D(m)
1	2588	0.67
2	647	1.35
3	288	2.02
4	162	2.69
5	104	3.37

Luminous flux luminaire  
1909 lm (EXTREME CUT OFF)

#### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable 1-10V, Dimmable DALI 1		

#### Physical

Color	Aluminum
Orientation	Fixed
Recessed depth (mm)	290
Weight (kg)	1.01

#### Note

Pre-installation frame. To be ordered separately.

## Light Supply Wall-Washer No Trim Dimmable



---

Pre-installation frame  
08.8137.00