









Light Supply Wall-Washer Trim

03.6613.3B - White/White

Recessed luminaire with LED light source. Remote 220/240V power supply included.

Indirect, Direct

Phosphor LED

Asymmetric

Wall Washer

Main specifications

 Number of heads
 1

 Lamp category
 LED

 Power (W)
 28W

 CCT (K)
 4000K

 CRI
 80

Net lumen (lm) 1918

MountingsCeiling recessedEnvironmentIndoor dry location

Optical

Lighting type LED type Light distribution Optical type

Down
Beam angle (°) 37
Beam angle C90-270 (°) 52

90°	90°
	L_1
	\ /
606	60°
	\times
K MAL	\times
	$\langle \ $
30° 2209 cd	30°
30 / 220/ Cd \	30 1

Luminous flux luminaire 1918 lm (EXTREME CUT OFF)

Beam Angle:		37°
h(m)	E(l ×)	D(m)
1	2209	0.76
2	552	1.53
3	245	2.29
4	138	3.06
5	88	3.82

Electrical

Frequency (Hz) 50/60 Insulation class Dimmable No

Driver Remote included
Driver type Non Dimmable
Emergency Without

Physical

Color White/White
Orientation Fixed
Recessed depth (mm) 290
Weight (kg) 1.01