

## Light Supply Wall-Washer Trim

■ 03.6614.1B - Black/White

Recessed luminaire with LED light source. Remote 220/240V power supply included.


Recessed luminaire with LED light source. Remote 220/240V power supply included.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1355
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	26W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	98		

### Optical

<b>Lighting type</b>	Indirect, Direct
<b>LED type</b>	Phosphor LED
<b>Light distribution</b>	Asymmetric
<b>Optical type</b>	Wall-washer
<b>Beam angle (°)</b>	38
<b>Beam angle C90-270 (°)</b>	52



<b>Beam Angle:</b>	38°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	1564	0.77	
2	391	1.55	
3	174	2.32	
4	98	3.09	
5	63	3.86	

Luminous flux luminaire  
1355 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	No		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic		

### Physical

<b>Color</b>	Black/White
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	290
<b>Weight (kg)</b>	1.01

### Certification / Marking

