









Light Supply Wall-Washer Trim

■ 03.6814.1BA - Black/White

Recessed luminaire with LED light source. Remote 220/240V power supply included.

Indirect, Direct

LED array

Asymmetric

Main specifications

 Number of heads
 1

 Lamp category
 LED

 Power (W)
 33.2W

 CCT (K)
 3000K

 CRI
 90

Net lumen (lm) 177 Mountings Ceil

MountingsCeiling recessedEnvironmentIndoor dry location

Optical

Lighting type LED type Light distribution Optical type

Optical type Wall Washer
Down
Beam angle (°) 36
Beam angle C90-270 (°) 51

90°	90°
	1
606	606
K X X X X X X X X X X X X X X X X X X X	
30° / 2092 cd	30°,

Luminous flux luminaire 1771 lm (EXTREME CUT OFF)

Without

Ш

Bea	m Angle:	36°
h(m)) E(l ×)	D(m)
1	2092	0.74
2	523	1.48
3	232	2.22
4	131	2.95
	Ω1	3 40

Electrical

Frequency (Hz) 50/60 Emergency
Voltage (V) 220.00 Insulation class
Dimmable No

DriverRemote includedDriver typeNon Dimmable

Physical

Color Black/White
Orientation Fixed
Recessed depth (mm) 290
Weight (kg) 1.01