


Light Supply Wall-Washer Trim Dimmable

03.6614.3B.DA - White/White

Recessed luminaire with LED light source. Remote 220/240V power supply included.

Recessed luminaire with LED light source. Remote 220/240V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	1355
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	26W	Environment	Indoor
CCT (K)	3000K		
CRI	98		

Optical

Lighting type	Indirect, Direct
LED type	Phosphor LED
Light distribution	Asymmetric
Optical type	Wall-washer
Beam angle (°)	38
Beam angle C90-270 (°)	52



Beam Angle:	38°
h(m)	E(lx) D(m)
1	1564 0.77
2	391 1.55
3	174 2.32
4	98 3.09
5	63 3.86

Luminous flux luminaire
1355 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic dimmable 1-10V, Electronic dimmable DALI		

Physical

Color	White/White
Orientation	Fixed
Recessed depth (mm)	290
Weight (kg)	1.01

Certification / Marking

