


## Light Supply Wall-Washer Trim Dimmable

■ □ 03.6812.1BADA - Black/White

Recessed luminaire with LED light source. Remote 220/240V power supply included.

Recessed luminaire with LED light source. Remote 220/240V power supply included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2142
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	33.2W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	80		

### Optical

<b>Lighting type</b>	Indirect, Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Asymmetric
<b>Optical type</b>	Wall-washer
<b>Beam angle (°)</b>	36
<b>Beam angle C90-270 (°)</b>	51



<b>Beam Angle:</b>	36°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	2531	0.74	
2	633	1.48	
3	281	2.22	
4	158	2.95	
5	101	3.69	

Luminous flux luminaire  
2142 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic dimmable 1-10V, Electronic dimmable DALI		

### Physical

<b>Color</b>	Black/White
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	290
<b>Weight (kg)</b>	1.01

### Certification / Marking

