

Light Tube Covered 1500 mm

New

03.8422.40 - White

Diffused direct shielded LED light module to be installed in the Infra-Structure Episode 2. Safety fixing and locking mechanical elements integrated for a transversal installation between two rods of the profile. The Light Tubes are only fed by one of the ends and do not communicate current through the other end. Each lighting element is...

Diffused direct shielded LED light module to be installed in the Infra-Structure Episode 2.

Safety fixing and locking mechanical elements integrated for a transversal installation between two rods of the profile.

The Light Tubes are only fed by one of the ends and do not communicate current through the other end.


Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	1351
Power (W)	35.5W	Mountings	Ceiling surface
System power (W)	38	Environment	Indoor dry location
CCT (K)	2700K		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	50
Beam angle C90-270 (°)	116
Efficiency (lm/W)	35.55



Beam Angle: 50°

h(m)	E(lx)	D(m)
1	900	0.94
2	225	1.87
3	100	2.81
4	56	3.74
5	36	4.68


Luminous flux luminaire
1351 lm

Electrical

Dimmable	Yes
Driver	Remote excluded
Emergency	Without
Insulation class	III

Physical

Color	White
Orientation	Fixed
Weight (kg)	3.4
Length (mm)	1500
Lifespan (L70 B10)	L80B50



Light Tube Covered 1500 mm



0/1-10V & Push 12-48V Dimmer
60.9395



Casambi Controller 220-240V. Remote
Installation
60.9392



LED Power Supply Source for remote
installation. 48V/320W. 100/240 Vac
60.8919



LED Power Supply Source for remote
installation. 48V. 100Vac (150W)-240Vac
(200W)
60.9607



LED power supply source for remote
installation, 48V/120W. 220/240 Vac
60.9170



DALI 12-48V Dimmer
60.9678