


Light Tube Covered 1500 mm

New

03.8425.14 - Black



Diffused direct shielded LED light module to be installed in the Infra-Structure Episode 2. Safety fixing and locking mechanical elements integrated for a transversal installation between two rods of the profile. The Light Tubes are only fed by one of the ends and do not communicate current through the other end. Each lighting element is...

Diffused direct shielded LED light module to be installed in the Infra-Structure Episode 2. Safety fixing and locking mechanical elements integrated for a transversal installation between two rods of the profile.


The Light Tubes are only fed by one of the ends and do not communicate current through the other end. Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.

Main specifications

Number of heads	1	Net lumen (lm)	751
Lamp category	LED	Mountings	Ceiling surface
Power (W)	35.5W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	48
Beam angle C90-270 (°)	103



Beam Angle: 48°

h(m)	E(lx)	D(m)
1	622	0.89
2	155	1.78
3	69	2.67
4	39	3.56
5	25	4.45

Luminous flux luminaire
751 lm



Electrical

Dimmable	Yes
Driver	Remote excluded
Emergency	Without
Insulation class	III

Physical

Color	Black
Orientation	Fixed
Length (mm)	1500

Light Tube Covered 1500 mm



LED power supply source for remote installation, 48V/120W. 220/240 Vac
60.9170

Casambi Controller 220-240V. Remote Installation
60.9392

LED Power Supply Source for remote installation. 48V. 100Vac (150W)-240Vac (200W)
60.9607



LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac
60.8919

0/1-10V & Push 12-48V Dimmer
60.9395

DALI 12-48V Dimmer
60.9678