


Light Tube Ø 30 Direct 1500 mm On Board Dimmer

03.8102.40 - White

Diffused LED light module to be installed in The Infra-Structure.




Main specifications

Number of heads	1	Net lumen (lm)	2329
Lamp category	LED	Mountings	Track
Power (W)	38W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	106
Beam angle C90-270 (°)	106



Beam Angle: 106°

h(m)	E(lx)	D(m)
1	571	7.49
2	143	14.98
3	63	22.47
4	36	29.96
5	23	37.45

Luminous flux luminaire
2329 lm

Electrical

Voltage (V)	48.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmer on board		
Emergency	Without		

Physical

Color	White
Orientation	Fixed
Weight (kg)	1.21
Length (mm)	1544

Note

System turning fastening elements 0°-90° with a magnetic connection and mechanic security bock for a transversally installation between two lines of the profile. The Light Tube are only fed by one od the ends and do not communicate current through the other end. For wireless lighting control, choose integrated Casambi versions.

