


## Light Tube Ø 30 Direct 900 mm Casambi integrated

New

■ **03.8100.14.CB - Black**

Diffused LED light module to be installed in The Infra-Structure.




### Main specifications

|                        |       |                       |        |
|------------------------|-------|-----------------------|--------|
| <b>Number of heads</b> | 1     | <b>Net lumen (lm)</b> | 1456   |
| <b>Lamp category</b>   | LED   | <b>Mountings</b>      | Track  |
| <b>Power (W)</b>       | 23W   | <b>Environment</b>    | Indoor |
| <b>CCT (K)</b>         | 2700K |                       |        |
| <b>CRI</b>             | 90    |                       |        |

### Optical

|                               |                |
|-------------------------------|----------------|
| <b>Lighting type</b>          | Direct         |
| <b>LED type</b>               | Top LED        |
| <b>Light distribution</b>     | Symmetric      |
| <b>Optical type</b>           | Diffused light |
| <b>Beam angle (°)</b>         | 106            |
| <b>Beam angle C90-270 (°)</b> | 106            |



Beam Angle: 150°

| h(m) | E(lx) | D(m)  |
|------|-------|-------|
| 1    | 357   | 7.49  |
| 2    | 89    | 14.98 |
| 3    | 40    | 22.47 |
| 4    | 22    | 29.96 |
| 5    | 14    | 37.45 |

Luminous flux luminaire  
1456 lm

### Electrical

|                         |         |
|-------------------------|---------|
| <b>Voltage (V)</b>      | 48.00   |
| <b>Dimmable</b>         | Yes     |
| <b>Driver</b>           | Remote  |
| <b>Emergency</b>        | Without |
| <b>Insulation class</b> | III     |

### Physical

|                    |       |
|--------------------|-------|
| <b>Color</b>       | Black |
| <b>Orientation</b> | Fixed |
| <b>Weight (kg)</b> | 0.78  |
| <b>Length (mm)</b> | 944   |

### Note

System turning fastening elements 0°-90° with a magnetic connection and mechanic security lock for a transversally installation between two lines of the profile. The Light Tube are only fed by one of the ends and do not communicate current through the other end. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

