


Light Tube Ø 30 Direct 900 mm Dali Version

03.8100.40.DA - White

Diffused LED light module to be installed in The Infra-Structure.




Main specifications

Number of heads	1	Net lumen (lm)	1456
Lamp category	LED	Mountings	Track
Power (W)	23W	Environment	Indoor
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	106
Beam angle C90-270 (°)	106



Beam Angle: 106°

h(m)	E(lx)	D(m)
1	357	7.49
2	89	14.98
3	40	22.47
4	22	29.96
5	14	37.45

Luminous flux luminaire
1456 lm

Electrical

Voltage (V)	48.00	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic dimmable DALI		
Emergency	Without		

Physical

Color	White
Orientation	Fixed
Weight (kg)	0.78
Length (mm)	944

Note

System turning fastening elements 0°-90° with a magnetic connection and mechanic security back for a transversally installation between two lines of the profile. The Light Tube are only fed by one od the ends and do not communicate current through the other end. For wireless lighting control, choose integrated Casambi versions.

