

Light Tube Ø 30 Indirect 1200 mm Dali Version

03.8116.40.DA - White


Diffused LED light module to be installed in The Infra-Structure.

Main specifications

Number of heads	1	CRI	90
Lamp category	LED	Net lumen (lm)	1624
Power (W)	30W	Mountings	Track
System power (W)	30	Environment	Indoor dry location
CCT (K)	3000K		

Optical

Lighting type	Indirect
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	93
Beam angle C90-270 (°)	99
UGRL	3
Efficiency (lm/W)	54.13



Beam Angle: 99°

h(m)	E(lx)	D(m)
1	695	2.12
2	174	4.25
3	77	6.37
4	43	8.50
5	28	10.62

Luminous flux luminaire
1624 lm

Electrical

Voltage (V)	48	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Dimmable DALI		
Emergency	Without		

Physical

Color	White
Orientation	Fixed
Weight (kg)	1
Length (mm)	1244
Lifespan (L70 B10)	L80B50

Note

System turning fastening elements 0°-90° with a magnetic connection and mechanic security back for a transversally installation between two lines of the profile. The Light Tube are only fed by one of the ends and do not communicate current through the other end. For wireless lighting control, choose integrated Casambi versions.

